

(43) International Publication Date
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number
WO 2005/012029 A1(51) International Patent Classification⁷: **B60L 11/18**,
B60K 6/04, H02J 7/14

[JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

(21) International Application Number:
PCT/JP2004/010276(74) Agent: ITEC INTERNATIONAL PATENT FIRM;
Pola-Nagoya Bldg., 9-26, Sakae 2-chome, Naka-ku,
Nagoya-shi, Aichi 4600008 (JP).

(22) International Filing Date: 13 July 2004 (13.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-203737 30 July 2003 (30.07.2003) JP

(71) Applicant (for all designated States except US): TOYOTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(72) Inventor; and

(75) Inventor/Applicant (for US only): NADA, Mitsuhiro

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: HYBRID POWER OUTPUT APPARATUS AND CONTROL METHOD



(57) Abstract: In response to the driver's release of an accelerator, the procedure of the invention sequentially compares an observed charge-discharge electric power W_b of a battery with two reference values W_{r1} and W_{r2} , which are set on the basis of an input restriction W_{in} of the battery. The procedure changes over a control mode among an ordinary state varying control (processing of and after step S160) to gradually lower a revolution speed N_e of an engine 22 with torque output, an idling state varying control (step S220) to gradually lower the revolution speed N_e of the engine 22 while idling the engine 22, and a fuel supply shutoff state varying control (step S230) to shut off fuel supply to the engine 22.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*